

# HYDROSCAND T7011



|                       |     |
|-----------------------|-----|
| Product group         | 110 |
| Safety factor         | 1:4 |
| Bundled pipes/hoses   | 1   |
| Cover tube resistance | ,   |
| Max temperature (°C)  | 100 |
| Reinforcement layers  | 1   |
| Min temperature (°C)  | -40 |

A light and flexible hose with a wide range of applications, such as hydraulics, chemicals, various types of gases ect. Low volumetric expansion. NOTE! Air and water max +70°C

|          | OD (mm) | Working pressure (MPa) | Bend radius (mm) | ID (inch) | ID (mm) | Weight (kg) |
|----------|---------|------------------------|------------------|-----------|---------|-------------|
| 10450102 | 8.3     | 21                     | 25               | 1/8"      | 3.5     | 0.05        |
| 10450103 | 9.6     | 21                     | 25               | 3/16"     | 5       | 0.06        |
| 10450104 | 12.2    | 21                     | 35               | 1/4"      | 6.5     | 0.1         |
| 10450105 | 14.3    | 19                     | 45               | 5/16"     | 8       | 0.13        |
| 10450106 | 16      | 16                     | 55               | 3/8"      | 10      | 0.15        |
| 10450108 | 20.3    | 14                     | 75               | 1/2"      | 13      | 0.22        |
| 10450112 | 27.1    | 9                      | 140              | 3/4"      | 19      | 0.33        |
| 10450116 | 34      | 7                      | 190              | 1"        | 25      | 0.46        |

