EGEFLEX 1



Product group	100
Cover tube resistance	,
Safety factor	1:4
Bundled pipes/hoses	1
Hose label	white
Max temperature (°C)	100
Reinforcement layers	1
Min temperature (°C)	-40

Ozone resistant hose for applications with medium/high pressures and much external abrasion. Equivalent to EN 853 1SN (25.0-4.0 MPa). The hose is approved by MSHA (flame resistant). Part numbers ending in -30 are supplied on a reel. Joints can occur, maximum 4 lengths/bobbin and a minimum length of 5 meters per length.

	ID (inch)	ID (mm)	OD (mm)	Working pressure (MPa)	Bend radius (mm)	Weight (kg)
11010003	3/16"	5	11.8	25	90	0.18
11010004	1/4"	6.5	13.4	22.5	100	0.23
11010005	5/16"	8	15	21.5	115	0.27
11010006	3/8"	9.5	17.4	18	130	0.34
11010008	1/2"	13	20.6	16	180	0.42
11010010	5/8"	16	23.7	13	200	0.49
11010012	3/4"	19	27.7	10.5	240	0.6
11010016	1"	25	35.6	8.8	300	0.89
11010020	1 1/4"	32	43.5	6.3	420	1.28
11010024	1 1/2"	38	50.6	5	500	1.52
11010032	2"	51	64	4	630	2.06

