

Kappaflex 2 CO Smooth



Product group	100
Safety factor	1:4
Bundled pipes/hoses	1
Cover tube resistance	, ,
Hose label	orange
Max temperature (°C)	100
Reinforcement layers	2
Min temperature (°C)	-40

Ozone resistant hose for applications with high pressures, well suited for marine applications. Exceeds EN 857 2SC. DNV-, MED- and MSHA-approved. Part numbers ending in -30 are supplied on a reel. Joints can occur, maximum 4 lengths/bobbin and a minimum length of 5 meters.

	ID (inch)	ID (mm)	OD (mm)	Working pressure (MPa)	Bend radius (mm)	Weight (kg)
11041704	1/4"	6.5	13.4	42.5	75	0.29
1104170430	1/4"	6.5	13.4	42.5	75	0.29
11041705	5/16"	8	15	40	85	0.34
11041706	3/8"	10	17.2	35	90	0.42
1104170630	3/8"	10	17.2	35	90	0.42
11041708	1/2"	13	20.4	31	130	0.58
1104170830	1/2"	13	20.4	31	130	0.58
11041710	5/8"	16	23.9	28	160	0.7
1104171230	3/4"	19	27.7	28	195	0.82
11041716	1"	25	35.4	21	250	1.19

