

Kappaflex 2K CO Rock



Product group	100
Safety factor	1:4
Bundled pipes/hoses	1
Cover tube resistance	, ,
Hose label	Grön med svart text
Certificate	, ,
Max temperature (°C)	100
Reinforcement layers	2
Min temperature (°C)	-50

This hose is suitable for applications with very high pressures (47.0-32.7 MPa). Exceeds EN 857 2SC (40.0 - 16.5 MPa).

	OD (mm)	Working pressure (MPa)	Bend radius (mm)	ID (inch)	ID (mm)	Weight (kg)
11056304	13.4	45	45	1/4"	6.5	0.27
1105630430	13.4	45	45	1/4"	6.5	0.27
11056305	15	42	60	5/16"	8	0.32
1105630530	15	42	60	5/16"	8	0.32
11056306	17.4	38.5	70	3/8"	10	0.38
1105630630	17.4	38.5	70	3/8"	10	0.38
11056308	20.6	34.5	90	1/2"	13	0.53
1105630830	20.6	34.5	90	1/2"	13	0.53
11056310	23.6	29	130	5/8"	16	0.66
11056312	27.7	28	160	3/4"	19	0.87
11056316	35.6	20	210	1"	25	1.17
11056320	43.5	17.5	300	1 1/4"	32	1.59

