

# INDUSTRIAL COOLING HOSE, FIBERGLASS



<b>Product group</b>	140
<b>Safety factor</b>	1:3
<b>Bundled pipes/hoses</b>	1
<b>Antistatic wire</b>	
<b>Flat coil</b>	
<b>Max temperature (°C)</b>	120
<b>Min temperature (°C)</b>	-30

Used as a protection and cooling hose where the working temperature is high, e.g. melting furnaces and foundries. The cover cord is made of fiberglass, which gives the hose a good resistance towards flames. Sustains 530° C temporary radiation as well as glowing steel spatter.

	OD (mm)	Bend radius (mm)	Working pressure (MPa)	ID (mm)	Length meter per coil	Weight (kg)
<b>14020008</b>	29	50	1.2	13	40	0.44
<b>14020010</b>	32	85	1.2	16	40	0.77
<b>14020012</b>	35	95	1.2	19	40	0.69
<b>14020016</b>	41	125	1.2	25	40	0.73
<b>14020020</b>	48	160	1.2	32	40	0.88
<b>14020024</b>	55	380	1.2	38	40	1.1
<b>14020026</b>	57	400	1.2	40	40	1.9
<b>14020030</b>	63	450	1.2	45	40	2.1
<b>14020032</b>	71	250	1.2	51	40	2.24
<b>14020040</b>	81	630	1.2	63.5	40	2.91
<b>14020048</b>	96	380	1.2	76	40	3.3

