

Radiator flex, corrugated cooling hose



Product group	140
Safety factor	1:3
Bundled pipes/hoses	1
Cover tube resistance	, ,
Antistatic wire	
Flat coil	
Max temperature (°C)	120
Min temperature (°C)	-40

The hose is used as a cooling hose in vehicles where there is a requirement for high flexibility. Its special corrugation allows hard bends without folding. Also used as a hot water hose in the industry.

	OD (mm)	Bend radius (mm)	Working pressure (MPa)	ID (mm)	Vacuum pr. Max%	Length meter per coil	Weight (kg)
14095008	22	50	0.5	13	80	40	0.35
14095010	25	60	0.5	16	80	40	0.39
14095012	29	70	0.5	20	80	40	0.46
14095014	31	75	0.5	22	80	40	0.52
14095016	34	85	0.5	25	80	40	0.57
14095020	41	105	0.5	32	80	40	0.75
14095022	44	115	0.5	35	80	40	0.81
14095024	47	130	0.5	38	80	40	0.87
14095026	51	140	0.5	42	80	40	0.95
14095030	54	150	0.5	45	80	40	1
14095032	60	165	0.5	51	80	40	1.12
14095039	70	200	0.5	60	80	40	1.7
14095040	73.5	210	0.5	63	80	40	1.8
14095044	80	220	0.5	70	80	40	1.87
14095048	86	250	0.5	76	80	40	2
14095051	90	270	0.5	80	80	40	2.15
14095056	101	300	0.5	90	80	40	2.3
14095064	113	340	0.5	102	80	40	2.7



OD (mm)	Bend radius (mm)	Working pressure (MPa)	ID (mm)	Vacuum pr. Max%	Length meter per coil	Weight (kg)
---------	------------------	------------------------	---------	-----------------	-----------------------	-------------

