VACOIL



Product group	140
Safety factor	1:3
Bundled pipes/hoses	1
Antistatic wire	
Flat coil	
Max temperature (°C)	55
Reinforcement layers	1
Min temperature (°C)	-25

Flexible suction and pressure hose for tank wagons, used for transportation of oil and gasoline.

	OD (mm)	Bend radius (mm)	Working pressure (Bar)	Working pressure (MPa)	ID (mm)	Vacuum pr. Max%	Length meter per coil	Weight (kg)
14332012	28	70	-	1.6	19	90	60	0.45
14332016	35.6	80	-	1.6	25	90	60	0.67
14332020	42.6	100	-	1.6	32	90	60	0.8
14332024	51	125	-	1.4	38	90	40	1.2
14332026	53	130	14	1.4	40	90	40	1.2
14332028	58	140	12	1.2	45	90	40	1.34
14332032	63	150	-	1.2	50	90	40	1.73
14332040	77	190	-	1	63	90	40	2.03
14332048	91	210	10	1	76	90	30	2.7
14332064	118	300	8	0.8	102	90	30	3.7
14332077	136	450	8	0.8	120	90	20	4.75
14332080	144	480	7	0.7	127	90	20	5.3
14332096	169.5	550	5	0.5	152	90	20	6.35



HYDROSCAND