

Exmarin, exhaust gas / marine refill hose



Product group	140
Safety factor	1:3
Bundled pipes/hoses	1
Antistatic wire	
Flat coil	
Certificate	,
Max temperature (°C)	100
Reinforcement layers	2
Min temperature (°C)	-30

The hose is suitable for exhaust gas and refill for boats. It fulfils the requirements ISO 7840A1. This means that it can sustain 2,5 minutes in open fire without leaking. It is also CE branded.

	Bend radius (mm)	Working pressure (MPa)	ID (mm)	Vacuum pr. Max%	Length meter per coil	OD (mm)	Weight (kg)
14340012	120	0.3	19	80	40	29	0.63
14340016	150	0.3	25	80	40	35	0.78
14340020	190	0.3	32	80	40	42	0.94
14340024	230	0.3	38	80	40	48	1.09
14340030	270	0.3	45	80	40	55	1.27
14340032	300	0.3	50	80	40	60	1.41
14340038	330	0.3	55	80	40	65	1.53
14340040	380	0.3	63.5	80	40	73.5	1.86
14340048	460	0.3	76	80	20	86	2.25
14340056	540	0.3	90	80	20	100	2.67
14340064	610	0.3	102	-	20	112	3.02
14340203	1,400	0.5	203	80	12	224	9.5

