R-FOUR, RETURN AND SUCTION HOSE, SAE 100 R4



Product group	140
Safety factor	1:4
Bundled pipes/hoses	1
Cover tube resistance	,
Antistatic wire	
Flat coil	
Max temperature (°C)	100
Reinforcement layers	2
Min temperature (°C)	-40

Suction and refill hose for hydraulic systems. Also suitable for low pressure hydraulics. The hose fulfils requirements according to SAE 100 R4.

	OD (mm)	Bend radius (mm)	Working pressure (MPa)	ID (mm)	Vacuum pr. Max%	Length meter per coil	Weight (kg)
14380010	25	80	2.1	15	90	40	0.5
14380012	30	120	2.1	19	90	40	0.61
14380014	32	130	1.7	22	90	40	0.65
14380016	36	145	1.7	25	90	40	0.82
14380020	43	195	1.4	32	90	40	1.08
14380024	50	250	1	38	90	40	1.27
14380026	54	275	0.8	42	90	40	1.4
14380032	62	300	0.7	50	90	40	1.6
14380039	74	350	0.4	60	90	40	2.35
14380040	76	355	0.4	63	90	40	2.41
14380048	90	455	0.4	76	90	40	3.15
14380064	116	610	0.2	102	90	40	4.4



HYDROSCAND