

# Vacuum hose, Polyurethane



|                             |     |
|-----------------------------|-----|
| <b>Product group</b>        | 140 |
| <b>Media description</b>    | , , |
| <b>Bundled pipes/hoses</b>  | 1   |
| <b>Flat coil</b>            |     |
| <b>Antistatic wire</b>      |     |
| <b>Max temperature (°C)</b> | 85  |
| <b>Min temperature (°C)</b> | -25 |

A hose suitable for ventilation; suction of gases, smoke, dust pellets; and for transportation of mineral wool insulation. The hose is internally smooth and very flexible. Also available in antistatic design, see 1463-40-xx. Food approved.

|          | Working pressure (MPa) | ID (mm) | Vacuum pr. Max% | Length meter per coil | OD (mm) | Thickness (mm) | Bend radius (mm) | Weight (kg) |
|----------|------------------------|---------|-----------------|-----------------------|---------|----------------|------------------|-------------|
| 14631016 | 0.06                   | 25      | 40              | 20                    | 26.2    | 0.5            | 25               | 0.19        |
| 14631020 | 0.06                   | 32      | 40              | 20                    | 33.2    | -              | 32               | 0.19        |
| 14631024 | 0.04                   | 38      | 30              | 20                    | 39.2    | -              | 38               | 0.25        |
| 14631030 | 0.04                   | 45      | 30              | 20                    | 46.2    | -              | 45               | 0.32        |
| 14631032 | 0.04                   | 50      | 30              | 20                    | 51.4    | -              | 50               | 0.39        |
| 14631039 | 0.04                   | 60      | 30              | 20                    | 61.4    | -              | 60               | 0.44        |
| 14631040 | 0.03                   | 63      | 30              | 20                    | 64.4    | -              | 65               | 0.47        |
| 14631048 | 0.03                   | 75      | 30              | 20                    | 76.4    | -              | 75               | 0.6         |
| 14631050 | 0.02                   | 80      | 30              | 20                    | 81.4    | -              | 80               | 0.65        |
| 14631055 | 0.02                   | 90      | 30              | 20                    | 91.6    | -              | 90               | 0.75        |
| 14631064 | 0.02                   | 100     | 30              | 20                    | 101.6   | -              | 100              | 0.85        |
| 14631080 | 0.02                   | 125     | 30              | 20                    | 126.6   | -              | 125              | 1.17        |
| 14631096 | 0.01                   | 152     | 30              | 20                    | 153.8   | -              | 150              | 1.45        |
| 14631160 | 0.01                   | 160     | 30              | 20                    | 161.8   | -              | 160              | 1.7         |
| 14631180 | 0.01                   | 180     | 30              | 10                    | 181.8   | -              | 180              | 2           |

