Blue silicon hose



Product group	140
Safety factor	1:3
Bundled pipes/hoses	1
Flat coil	
Antistatic wire	
Max temperature (°C)	180
Min temperature (°C)	-50

Excellent hose for cool and heat systems in buses and trucks. The silicon may come into contact with oil, but should NOT be used as a transporter hose for petroleum products, nor in oil baths.

	ID (mm)	Length meter per coil	OD (mm)	Working pressure (MPa)	Weight (kg)
15091004	6	1	15	0.88	0.31
15091006	10	1	19	0.83	0.34
15091008	13	1	21	0.79	0.36
15091010	16	1	25	0.75	0.43
15091011	18	1	27	0.67	0.46
15091012	19	1	28	0.66	0.48
15091014	22	1	31	0.61	0.54
15091016	25	1	34	0.58	0.59
15091018	28	1	37	0.57	0.63
15091019	30	1	39	0.55	0.68
15091020	32	1	41	0.53	0.72
15091022	35	1	44	0.51	0.76
15091024	38	1	47	0.49	0.79
15091025	40	1	50	0.48	0.81
15091026	41	1	49.4	0.4	0.83
15091030	45	1	54	0.47	0.87
15091031	48	1	57	0.33	0.95
15091032	51	1	60	0.37	1.05
15091038	55	1	65	0.31	1.21



HYDROSCAND

	ID (mm)	Length meter per coil	OD (mm)	Working pressure (MPa)	Weight (kg)
15091039	60	1	70	0.27	1.29
15091040	64	1	73	0.23	1.35
15091044	70	1	80	0.22	1.49
15091048	76	1	86	0.21	1.58
15091051	80	1	90	0.18	1.66
15091053	83	1	93	0.17	1.72
15091056	89	1	100	0.15	1.85
15091064	102	1	113	0.13	2.32
15091072	114	1	122.4	0.2	0.1
15091080	127	1	138	0.11	2.86
15091096	152	1	163	0.09	3.42

