

Low-weight spiral suction hose



Product group	140
Bundled pipes/hoses	1
Safety factor	1:3
Flat coil	
Antistatic wire	
Max temperature (°C)	60
Reinforcement layers	1
Min temperature (°C)	-5

A low-weight PVC hose for suction and pressure applications. The hose is also suitable for powder transportation within agriculture, food industry and gardening. Smooth inner tube. Sustains alcohols beneath 28%. Available in antistatic version, see 1552-10.

	Working pressure (MPa)	ID (mm)	Vacuum pr. Max%	Length meter per coil	OD (mm)	Bend radius (mm)	Weight (kg)
15520012	0.7	20	70	50	27	80	0.28
15520016	0.7	25	70	50	31	100	0.35
15520019	0.5	30	70	50	37	120	0.41
15520020	0.5	32	70	50	39	128	0.46
15520024	0.5	38	70	50	45	152	0.57
15520025	0.5	40	70	50	47	160	0.59
15520030	0.6	45	70	50	52	200	0.78
15520032	0.5	50	70	50	58	200	0.83
15520040	0.4	65	70	50	74	260	1
15520044	0.4	70	70	50	79	280	1.13
15520048	0.4	76	70	50	85	300	1.45
15520056	0.6	90	70	25	100	415	1.75
15520064	0.3	100	70	25	115	400	2.15
15520069	0.3	110	50	25	122	440	2.25
15520080	0.4	127	50	25	138	690	3.65
15520096	0.3	152	50	25	164	800	5.1
15520200	0.3	203	50	10	217	1,250	7.85

