

# Exhaust hose for hot air, Neoprene, double coated



|                      |     |
|----------------------|-----|
| Product group        | 140 |
| Bundled pipes/hoses  | 1   |
| Antistatic wire      |     |
| Flat coil            |     |
| Max temperature (°C) | 135 |
| Reinforcement layers | 1   |
| Min temperature (°C) | -35 |

A hose suitable for transportation of hot steams, smoke and exhaust gases. Low-weight and extremely flexible, good in tight areas. The hose is non-inflammable and has good chemical resistance. Other dimensions are available on request.

|          | Bend radius (mm) | Working pressure (MPa) | ID (mm) | Vacuum pr. Max% | Length meter per coil | Weight (kg) |
|----------|------------------|------------------------|---------|-----------------|-----------------------|-------------|
| 15611016 | 14               | 0.28                   | 25      | 7               | 4                     | 0.15        |
| 15611020 | 20               | 0.27                   | 32      | 6               | 4                     | 0.17        |
| 15611029 | 27               | 0.26                   | 44      | 5               | 4                     | 0.26        |
| 15611032 | 31               | 0.26                   | 51      | 5               | 4                     | 0.29        |
| 15611040 | 37               | 0.24                   | 63      | 5               | 4                     | 0.36        |
| 15611048 | 43               | 0.21                   | 76      | 4               | 4                     | 0.46        |
| 15611055 | 50               | 0.2                    | 89      | 4               | 4                     | 0.53        |
| 15611064 | 56               | 0.19                   | 102     | 3               | 4                     | 0.6         |
| 15611080 | 70               | 0.14                   | 127     | 3               | 4                     | 0.86        |
| 15611096 | 82               | 0.12                   | 152     | 2               | 4                     | 1.1         |
| 15611180 | 95               | 0.1                    | 180     | 1               | 4                     | 1.28        |
| 15611203 | 108              | 0.07                   | 203     | 1               | 4                     | 1.43        |

