

Polyurethane hose L 0.4



Product group	140
Bundled pipes/hoses	1
Antistatic wire	
Flat coil	
Max temperature (°C)	90
Min temperature (°C)	-40

A very light weighted hose delivered in a "compact"-package. The hose is very durable and suitable for the food and pharmaceutical industries. Areas of usage: Ventilation, pellet burner, oil mist. The hose is resistant to hydrolysis and microbes.

	Length meter per coil	OD (mm)	Bend radius (mm)	ID (mm)	Vacuum pr. Max%	Weight (kg)
15632032	6	56	26	51	16	0.18
15632040	6	68	32	63	14	0.22
15632048	6	81	38	76	10	0.3
15632050	6	87	40	82	10	0.32
15632055	6	95	45	90	7	0.35
15632064	6	107	51	102	7	0.41
15632070	6	115	55	110	7	0.44
15632073	6	120	57	115	7	0.46
15632080	6	132	64	127	7	0.5
15632085	6	145	70	140	5	0.55
15632096	6	157	76	152	5	0.78
15632130	6	135	65	130	5	0.68
15632160	6	165	80	160	5	0.69
15632170	6	175	85	170	5	0.73
15632180	6	185	90	180	5	0.91
15632203	6	208	102	203	5	1.05
15632228	6	233	115	228	5	1.13
15632254	6	259	127	254	2	1.25
15632300	6	305	150	300	2	1.3



	Length meter per coil	OD (mm)	Bend radius (mm)	ID (mm)	Vacuum pr. Max%	Weight (kg)
15632305	6	310	153	305	2	1.34
15632318	6	320	158	315	2	1.38
15632325	6	330	163	325	2	1.42
15632350	6	355	175	350	2	1.53
15632400	6	405	200	400	2	1.74
15632408	6	413	205	408	2	2.1
15632630	6	635	425	630	1	4.22

