Polyurethane hose H 1.4



Product group	140
Bundled pipes/hoses	1
Antistatic wire	
Flat coil	
Max temperature (°C)	90
Min temperature (°C)	-40

A very powerful PU-hose for transportation of strong abrasive particles. The hose is suitable for industrial vacuum cleaning, granulates and splinters. It is also resistant to oil mist and microbes.

	OD (mm)	Bend radius (mm)	Working pressure (MPa)	ID (mm)	Vacuum pr. Max%	Length meter per coil	Weight (kg)
15635020	41	60	0.36	32	92	10	0.39
15635022	44	65	0.34	35	92	10	0.42
15635024	47	69	0.31	38	82	10	0.46
15635025	49	72	0.31	40	82	10	0.49
15635032	61	87	0.29	51	82	10	0.71
15635038	65	95	0.28	55	76	10	0.77
15635040	73	111	0.24	63	66	10	0.86
15635044	80	117	0.23	70	66	10	0.97
15635048	87	126	0.2	76	59	10	1.06
15635050	91	132	0.2	80	59	10	1.11
15635064	112	165	0.15	102	44	10	1.48
15635076	131	194	0.13	120	31	10	1.75
15635080	138	203	0.13	127	31	10	1.91
15635096	163	242	0.11	152	26	10	2.29
15635160	171	255	0.09	160	25	10	2.51
15635175	186	278	0.09	175	18	10	2.74
15635203	215	321	0.08	203	18	10	3.5
15635220	232	353	0.06	220	12	10	3.65
15635250	263	390	0.06	250	12	10	3.91



HYDROSCAND

	OD (mm)	Bend radius (mm)	Working pressure (MPa)	ID (mm)	Vacuum pr. Max%	Length meter per coil	Weight (kg)
15635300	313	465	0.05	300	12	10	4.94
15635350	363	540	0.05	350	7	10	6.98
15635400	413	615	0.03	400	7	10	7.95
15635450	463	690	0.03	450	7	10	8.94

