

Polyurethane hose HD T 2.0



Product group	140
Bundled pipes/hoses	1
Flat coil	
Antistatic wire	
Max temperature (°C)	90
Min temperature (°C)	-40

An extremely powerful PU-hose for both suction and pressure transports of abrasive materials such as sand, granulates and splinters. The hose is suitable in the contractor business area, the wood and plastic industries.

	Working pressure (MPa)	ID (mm)	Vacuum pr. Max%	Length meter per coil	OD (mm)	Bend radius (mm)	Weight (kg)
15637025	0.43	40	94	10	50	100	0.76
15637032	0.4	51	94	10	61	125	1
15637038	0.38	55	89	10	65	140	1.1
15637039	0.36	60	89	10	70	150	1.32
15637048	0.29	76	89	10	87	190	1.51
15637056	0.24	90	89	10	103	225	1.81
15637064	0.21	102	87	10	115	250	2.13
15637070	0.2	110	87	10	124	275	2.82
15637096	0.15	152	82	10	167	450	4.08
15637160	0.14	160	81	10	175	500	4.81
15637170	0.12	170	80	10	185	600	5.1
15637200	0.1	200	0.85	10	217	800	6.43
15637203	0.11	203	66	10	220	950	6.43
15637250	0.09	250	51	10	267	1,300	7.91
15637300	0.06	300	42	10	317	1,600	9.45

