

Concrete pump hose, 85 bar



| | |
|----------------------|-----|
| Product group | 140 |
| Safety factor | 1:2 |
| Bundled pipes/hoses | 1 |
| Antistatic wire | |
| Flat coil | |
| Max temperature (°C) | 80 |
| Min temperature (°C) | -35 |

A hose suitable for placing and transporting concrete from beam. The very robust design prevents kink in the hose and makes it easy to use as well as flexible. It sustains high pressures. Deliverance usually fully assembled with fluid connectors. The pre-assembling is done in-house in Sweden.

| | Length meter per coil | OD (mm) | Bend radius (mm) | Working pressure (MPa) | ID (mm) | Weight (kg) |
|----------|-----------------------|---------|------------------|------------------------|---------|-------------|
| 14645032 | 40 | 70 | 360 | 8.5 | 50.8 | 3 |
| 14645040 | 40 | 87 | 420 | 8.5 | 65 | 3.15 |
| 14645048 | 40 | 97 | 460 | 8.5 | 75 | 4.9 |
| 14645051 | 40 | 104 | 480 | 8.5 | 80 | 5.3 |
| 14645064 | 40 | 125.6 | 520 | 8.5 | 101.6 | 7.1 |
| 14645080 | 40 | 151 | 620 | 8.5 | 125 | 9.1 |

