

Gas exhaust hose, stainless steel



Product group 140
Antistatic wire
Flat coil
Max temperature (°C) 700

Spiral wired gas exhaust hose with round cross section and labyrinth profile for e.g. exhaust gases, pellets and granulates. Can also be used as mechanical cable protection.

	Bend radius (mm)	ID (mm)	OD (mm)	Weight (kg)
14800012	70	20	24	0.5
14800014	77	22	26	0.55
14800016	86	25	29	0.62
14800019	101	30	34	0.73
14800020	160	32	37	0.77
14800022	170	35	40	0.97
14800024	190	38	43	1.05
14800025	200	40	45	1.1
14800026	210	42	47	1.15
14800032	250	50	55	1.23
14800038	265	55	60	1.35
14800039	275	60	65	1.46
14800040	285	65	70	1.58
14800044	300	70	75	1.7
14800048	310	75	80	1.81
14800051	320	80	85	1.93
14800053	335	85	90	2.14
14800056	345	90	95	2.17
14800062	375	100	105	2.4
14800064	380	102	107	2.45



	Bend radius (mm)	ID (mm)	OD (mm)	Weight (kg)
14800068	390	105	110	2.66
14800070	400	110	115	2.64
14800074	415	115	120	2.75
14800079	435	125	130	2.99
14800080	445	127	132	3.04
14800082	450	130	135	3.11
14800085	475	140	145	3.56
14800096	500	150	155	3.58
14800160	525	160	165	5.43
14800175	560	175	175	4.17
14800190	595	190	195	6.4
14800200	620	200	205	4.75
14800225	750	225	230	5.34
14800300	1,000	300	305	7.1

