

AQUASEWER, FLUSHING HOSE THERMOPLAST, 250 BAR



Product group	140
Safety factor	1:2.5
Bundled pipes/hoses	1
Antistatic wire	
Flat coil	
Max temperature (°C)	60
Reinforcement layers	2
Min temperature (°C)	-40

A hose suitable for high pressure sewage systems. The hose has low weight compared to rubber hoses, which leads to less abrasion and increased flowing speed. The hose sustains 3–4 times more external abrasion compared to a traditional rubber hose. It is delivered pre-assembled with fittings according to demand. Delivered with Pressure Test Certificate.

	OD (mm)	Bend radius (mm)	Working pressure (MPa)	ID (mm)	Length meter per coil	Weight (kg)
14190608	22.8	75	25	13	60	0.29
14190612	30.3	120	25	19.6	60	0.49
14190616	37.9	155	25	25.9	60	0.62
14190808	22.8	75	25	13	80	0.29
14190812	30.3	120	25	19.6	80	0.49
14190816	37.9	155	25	25.9	80	0.62
14191208	22.8	75	25	13	120	0.29
14191212	30.3	120	25	19.6	120	0.49
14191216	37.9	155	25	25.9	120	0.62
14191220	45.3	240	25	32.4	120	0.74
14191512	30.3	120	25	19.6	150	0.49
14191516	37.9	155	25	25.9	150	0.58
14191520	45.3	240	25	32.4	150	0.74

