

Polyurethane hose 2,5 mm

Performance



Product group	140
Bundled pipes/hoses	1
Antistatic wire	
Flat coil	
Max temperature (°C)	90
Min temperature (°C)	-40

	Length meter per coil	OD (mm)	Bend radius (mm)	Weight (kg/m)	Working pressure (MPa)	ID (mm)	Vacuum pr. Max%	Weight (kg)
156315200	10	215	840	5	0.08	200	55	5
15631524	10	50	130	0.8	0.44	38	94	0.8
15631525	10	52	135	0.8	0.43	40	94	0.8
156315250	10	266	1,050	7.1	0.04	250	-	7.1
15631530	10	57	155	1	0.41	45	94	1
15631532	10	66	170	1.2	0.4	51	94	1.2
15631538	10	72	175	1.3	0.38	55	94	1.3
15631539	10	77	185	1.5	0.37	60	94	1.5
15631540	10	82	190	1.6	0.35	65	94	1.6
1563154090	20	92	245	1.87	0.32	65	94	1.87
15631548	10	93	250	1.9	0.32	76	94	-
1563154890	20	93	250	1.9	0.32	76	94	-
15631551	10	97	270	2.1	0.29	80	94	-
15631556	10	107	285	2.4	0.27	90	94	-
15631564	10	119	300	2.6	0.25	102	94	-
1563156490	20	119	300	2.6	0.25	102	94	-
15631580	10	144	350	3.3	0.2	127	94	-
15631585	10	154	370	3.46	0.18	140	94	-

